



Technical Data Sheet

UPDATE: April 13, 2011
Make sure you have an updated data sheet on hand.
Canada and U.S. dial **1-866-212-1611** or (450) 624-1611

DESCRIPTION: **GATOR CLEAN RUBBER, PAINT AND TAR REMOVER** is effective in removing rubber, paint and tar from the surface of concrete pavers and natural stones.

FEATURES:

- Washes off with water
- Easy to use

FOR USE ON: For concrete pavers and natural stones that are warm to the touch

PLEASE NOTE:

- 1) This product dissolves sealants.
- 2) Do not let product dry up on concrete pavers.
- 3) Wear goggles and rubber gloves.
- 4) Use at above 16°C / 60°F

APPLICATION INSTRUCTIONS:

- 1) Apply product on stain
- 2) Let it soak for 5 minutes.
- 3) Apply product again.
- 4) Immediately scrub with hard bristle brush.
- 5) Repeat steps 3 & 4 until stain dissolves.
- 6) Rinse thoroughly with water.

PACKAGING:

Product	Retail size	Per box	Per Pallet
GATOR Rubber, Paint & Tar Remover	946ml (1 Qt.)	6 units	8 boxes

LIMITED WARRANTY:

Alliance Designer Products cannot guarantee results as it has no control over surface preparation and product application. If this product is proven to be defective, on the condition that it was applied pursuant to the required method of application and surface preparation, the sole obligation of Alliance Designer Products is to refund the purchase price. Proof of purchase is required for any claim. Alliance Designer Products shall not be liable for any other damages whatsoever, direct or consequential. To the extent permitted by law, Alliance Designer Products excludes any implied warranty of quality, merchantability or fitness for purpose.



GATOR RUBBER, PAINT & TAR REMOVER

TDS Revision Date (dd/mm/yyyy): 13/04/2011



*Please store container at above 0°C / 32°F.

CONTENTS HARMFUL. DANGEROUS FUMES FORM WHEN MIXED WITH OTHER PRODUCTS. MAY IRRITATE EYES. MAY IRRITATE SKIN. FUMES MAY CATCH FIRE. Do not mix with other household chemicals. Do not swallow. Do not breathe fumes. Do not get in eyes. Do not get on skin or clothing. Do not smoke. Keep out of reach of children. Wear a mask. Use only in a well ventilated area. Keep away from flames, such as a pilot light, and any object that sparks, such as an electric motor.

FIRST AID TREATMENT :

Contains Xylenes, 2-Butoxyethanol, Isopropanol and Alkylated benzene. If swallowed, call a Poison Control Centre or doctor immediately. Do not induce vomiting. If in eyes, rinse with water for at least 15 minutes. If on skin, rinse well with water.



DANGER
POISON IRRITANT FLAMMABLE