

All Surface Cleaner

multiple-use cleaner & degreaser

DESCRIPTION AND USE

Stand Off® All Surface Cleaner is a revolutionary formula for cleaning and degreasing heavily soiled stone, tile and masonry. It's ideal for concrete and other hard surfaces stained and soiled by hard use and heavy traffic. It's extremely dilutable for application to nearly any surface. In concentrate, it dissolves the toughest stains. All Surface Cleaner rinses quickly and efficiently with cold water, making it as easy to use as it is effective.

ADVANTAGES

- Easy to use.
- Powerful, economical concentrate.
- Flexible dilution with up to 10 parts water.
- Rinses fast and easy with cold water.
- Ideal for natural stone—from limestone to granite.
- Works on an enormous variety of surfaces.

TYPICAL TECHNICAL DATA

FORM: Clear blue liquid
 SPECIFIC GRAVITY: 1.070
 TOTAL SOLIDS: NA
 pH: 10.5 Typical Rinsewater 7.8 – 8.2
 WT./GAL.: 8.9 lbs.
 FLASH POINT: >200°F (> 93°C) ASTM D 3278
 FREEZE POINT: 32°F (0°C)

PREPARATION

Protect people, vehicles, plants, nearby property and non-masonry surfaces from contact with product, splash, spray, fumes or wind drift. Test all surfaces that may come in contact for compatibility. Immediately rinse nontarget materials with large quantities of water. Grass and plantings may be protected with sprinklers. Divert pedestrian and auto traffic if necessary. Clean when traffic is at a minimum.

Surface and Air Temperatures

Cleaning when temperatures are below freezing or will be overnight may harm masonry. Best air and surface temperatures for cleaning are 50°F (10°C) or above. If freezing conditions have existed before cleaning, let masonry thaw.

Equipment

Apply by spray, brush, sponge, or mop. Scrub heavily soiled surfaces with a nonabrasive brush or synthetic scrubbing pad. Rinse thoroughly with fresh water.

When cleaning porous surfaces, pressure water rinsing equipment fitted with a fan spray tip (15° minimum) and generating 400-1200 psi at a flow rate of 4-6 gallons (15-23 liters) per minute is most effective. Heated water (150-180°F; 66-82°C) may improve cleaning efficiency. Reduce rinsing pressure when cleaning delicate surfaces.

APPLICATION

Before use, read “Preparation” and “Safety Information.”

ALWAYS TEST each type of masonry surface and each type of stain for suitability, dilution and results. Use the following application instructions.

Dilution

Use All Surface Cleaner in concentrate to remove heavy soiling. When used as a light duty cleaner, dilute up to 1 part cleaner to 10 parts clean water.

All Surface Cleaner is recommended for these substrates. Always test. Coverage is in sq.ft./m. per gallon.			
Substrate	Type	Use?	Coverage
Architectural Concrete Block	Burnished	yes	50-150 sq.ft. 5-14 sq.m.
	Smooth	yes	
	Split-faced	yes	
	Ribbed	yes	
Concrete	Brick	yes	50-150 sq.ft. 5-14 sq.m.
	Tile	yes	
	Precast Panels	yes	
	Pavers	yes	
	Cast-in-place	yes	
Fired Clay	Brick	yes	150-500 sq.ft. 14-46 sq.m.
	Tile	yes	
	Terra Cotta	yes	
	Pavers	yes	
Marble, Travertine, Limestone	Polished	yes	500-1000 sq.ft. 46-93 sq.m.
	Unpolished	yes	150-500 sq.ft. 14-46 sq.m.
Granite	Polished	yes	500-1000 sq.ft. 46-93 sq.m.
	Unpolished	yes	150-500 sq.ft. 14-46 sq.m.
Sandstone	Unpolished	yes	150-500 sq.ft. 14-46 sq.m.
Slate	Unpolished	yes	150-500 sq.ft. 14-46 sq.m.

Always test to ensure desired results. Coverage estimates depend on surface texture and porosity.

All Surface Cleaner

Application Instructions

1. Prewet the surface with clean water.
2. Apply the appropriately diluted All Surface Cleaner to the masonry surface using a brush or low-pressure spray.
3. Let the cleaner stay on the surface for 5-15 minutes. Gently scrub heavily soiled areas.

Note: Do not let All Surface Cleaner dry on the surface. If drying occurs, lightly wet surfaces with fresh water. Reapply the cleaner scrubbing gently.

4. Rinse the surface thoroughly with clean water.
5. Repeat steps 1 through 4 if necessary.

Clean Up

Clean tools and equipment using fresh water.

SAFETY INFORMATION

Caution. Causes eye, skin and respiratory irritation. May be harmful if swallowed. For use by professional applicators only. Keep out of the reach of children.

Precautions

Contains: alcohol ethoxylates and chelating agent. Do not get in eyes, mouth, nose, skin or clothing. Wear rubber gloves, goggles or a face shield and other protective clothing as necessary to avoid contact. Wear a NIOSH-approved dust/mist respirator as needed to avoid breathing mists. Wash thoroughly after use. Concentrated product is mildly alkaline. Test all surfaces that may be in contact with product or rinsewater for suitability. Rinse accidental over-spray off immediately with large quantities of water. Avoid atomizing product during application and cleaning. Read the Material Safety Data Sheet and label for additional cautionary information. Always read the product label thoroughly before use.

First Aid

Ingestion: If conscious, give large amounts of water and call a physician, emergency room or poison control center immediately. Induce vomiting with instruction by medical personnel.

Eye Contact: Rinse thoroughly for 15 minutes. Get medical assistance if irritation persists.

Skin Contact: Remove contaminated clothing and rinse thoroughly. Get medical attention if irritation persists. Launder contaminated clothing before reuse.

Inhalation: Remove to fresh air. Get medical attention as necessary.

24-hour Emergency Information: INFOTRAC at 800-535-5053

Storage and Handling: Do not alter or use for purposes other than specified. Must be stored and transported upright with lid tightly in place. Store in cool, dry place. Keep containers tightly closed when not dispensing. Do not reuse container. Completely empty container before disposal in a sanitary landfill. **If spilled,** absorb with inert media and dispose in accordance with local, state and federal regulations.

Shelf Life: 3 years from date of manufacture in unopened container.

WARRANTY

The information and recommendations made are based on our own research and the research of others, and are believed to be accurate. However, no guarantee of their accuracy is made because we cannot cover every possible application of our products, nor anticipate every variation encountered in masonry surfaces, job conditions and methods used. The purchasers shall make their own tests to determine the suitability of such products for a particular purpose.

PROSOCO, Inc. warrants this product to be free from defects.

Where permitted by law, PROSOCO makes no other warranties with respect to this product, express or implied, including without limitation the implied warranties of merchantability or fitness for particular purpose. The purchaser shall be responsible to make his own tests to determine the suitability of this product for his particular purpose. PROSOCO's liability shall be limited in all events to supplying sufficient product to re-treat the specific areas to which defective product has been applied. Acceptance and use of this product absolves PROSOCO from any other liability, from whatever source, including liability for incidental, consequential or resultant damages whether due to breach of warranty, negligence or strict liability. This warranty may not be modified or extended by representatives of PROSOCO, its distributors or dealers.

CUSTOMER CARE

Factory personnel are available for product, environment and job-safety assistance with no obligation. Call 800-255-4255 and ask for Customer Care – technical support.

Factory-trained representatives are established in principal cities throughout the continental United States. Call Customer Care at 800-255-4255, or visit our web site at www.prosoco.com, for the name of the Stand Off[®] representative in your area.