

**DESCRIPTION AND USE**

Enviro Klean® Safety Klean is an effective, safe alternative to acidic compounds for cleaning brick, tile and concrete surfaces. Safety Klean rids new masonry construction of excess mortar, dirt and other common job site soiling. It's ideal for projects where traditional acidic cleaners are not allowed. Non-fuming Safety Klean contains no hydrochloric or other traditional inorganic acids and is safe for use on and around most metal surfaces, indoors or out. It is up to 70 percent more effective than citric and glycolic acids, and 50 percent more effective than phosphoric acid.

**ADVANTAGES**

- Proven effective for cleaning mortar smears and other common construction soiling.
- Replaces traditional mineral and organic acid products.
- Low odor and water-rinsable.
- Non-fuming.
- Environmentally responsible.
- Suitable for interior cleaning.

**Limitations**

- Not suitable for polished marble, limestone or travertine.
- Can cause discoloration and corrosion on certain types of metals. ALWAYS TEST.

**TYPICAL TECHNICAL DATA**

FORM: Clear amber liquid  
 SPECIFIC GRAVITY: 1.18  
 TOTAL SOLIDS: NA  
 pH: 0.334 @ 1:3 dilution  
 WT./GAL.: 9.56 lbs.  
 FLASH POINT: > 200°F (> 93°C)  
 FREEZE POINT: < -22°F (< -30°C)

**PREPARATION**

Protect people, vehicles, property and all surfaces not set for cleaning from product, splash, wind drift, residue, and rinsewater. When possible, finish cleaning before installing windows, doors, light fixtures, hardware, surrounding metal and other items that may be damaged by cleaning. If already in place, protect. Extended contact with the cleaning solution or its vapors may result in discoloration or damage. All caulking and sealant materials should be in place and thoroughly cured before cleaning.

**Surface and Air Temperatures**

To avoid harm to masonry, do not clean when temperatures are below freezing or will be overnight. Best cleaning results are obtained when air and masonry surface temperatures are 40°F (4°C) or above. If freezing conditions exist prior to application, allow adequate time for masonry to thaw.

**APPLICATION**

Before use, read "Preparation" and "Safety Information." ALWAYS TEST (minimum 4 ft. x 4 ft. area) for dilution rates, surface compatibility and desired results. Test each surface and each type of soiling using the following application instructions. Let test dry thoroughly before inspection.

**Dilutions**

Safety Klean may be diluted with up to three parts clean water, depending on the nature and severity of soiling. Always pour cold water into empty bucket first, then carefully add concentrate.

**Application Instructions**

**Exterior Applications**

1. Use clean water to thoroughly prewet surface to be cleaned.
2. Apply liberally using low pressure spray (50 psi max), roller or densely filled (tampico) masonry washing brush. Do not apply with high pressure spray. Do not atomize.

<b>Enviro Klean® Safety Klean is recommended for these substrates. Always test. Coverage is in sq.ft./m. per gallon of concentrate.</b>			
<i>Substrate</i>	<i>Type</i>	<i>Use?</i>	<i>Coverage</i>
<b>Architectural Concrete Block</b>	Smooth	yes	300-400 sq.ft. 28-37 sq.m.
	Split-faced	yes	
	Burnished	yes	
	Ribbed	yes	
<b>Concrete</b>	Brick	yes	600-1100 sq.ft. 56-102 sq.m.
	Tile	yes	
	Precast Panels	yes	
	Pavers	yes	
	Cast-in-place	yes	
<b>Fired Clay</b>	Brick	yes	500-900 sq.ft. 46-84 sq.m.
	Tile	yes	
	Terra Cotta	yes	
	Pavers	yes	
<b>Marble, Travertine, Limestone</b>	Polished	no	NA
	Unpolished	no	NA
<b>Granite</b>	Polished	yes	600-1200 sq.ft. 56-111 sq.m.
	Unpolished	yes	600-1200 sq.ft. 56-111 sq.m.
<b>Sandstone</b>	Unpolished	yes	600-900 sq.ft. 56-84 sq.m.
<b>Slate</b>	Unpolished	yes	600-1100 sq.ft. 56-102 sq.m.

Always test to ensure desired results.  
Coverage rates vary with surface texture, porosity and soiling conditions.

3. Let the cleaning solution dwell 3-5 minutes. Reapply. Light scrubbing of the surface improves cleaning results especially where high pressure rinsing equipment is not available. Do not let cleaning solution “dry into” the masonry. If solution starts to dry, reapply.
4. Rinse the cleaned area thoroughly using high pressure spray. Rinse with clean water from the bottom to the top, covering each section of the surface with a concentrated stream of water. To avoid streaking on vertical walls, take care to keep the wall below wet and rinsed free of cleaner and residues.

Note: Thorough rinsing is extremely important. As much water pressure as possible (without damaging the surface) should be used to ensure that all staining elements are completely removed. High pressure rinsing equipment with at least 600-1000 psi and 15-30 degree fan tip will prove most effective.

### Interior Applications

Proper ventilation is necessary. Follow exterior application procedures. If pressure rinsing isn't possible, use a sponge or soft-fibered brush to rinse thoroughly with clean water.

### Clean Up

Clean equipment with fresh water.

### Maintenance

Application of a “breathable” water repellent to the cleaned masonry surface reduces absorption of stain producing elements, keeping the surface clean for a longer period of time and making future cleaning operations faster and easier. For more information about water repellents for various surfaces, visit [www.prosoco.com](http://www.prosoco.com) or call PROSOCO toll-free at 800-255-4255 regarding Sure Klean® Weather Seal products.

## SAFETY INFORMATION

Danger. Corrosive to eyes. Harmful or fatal if ingested. Carefully read entire label for cautionary information.

### Precautions

**Contains:** Organic salt and cationic surfactant. Do not get in eyes. Avoid skin contact. Prolonged contact causes skin irritation. Avoid breathing mists. Mists may cause respiratory irritation. Do not breathe the vapors or mist. If mists are present, wear an appropriate dust/mist respirator. Wear gloves, and splash goggles or a face shield. Wear protective clothing and shoes as needed to prevent prolonged skin contact. Wash thoroughly after handling. Refer to the MSDS for additional precautionary information.

**Storage and Handling:** Keep container tightly closed when not dispensing product. Store away from other chemicals, heat and open flames in cool, dry place with adequate ventilation. Dilution and application equipment should be of polypropylene or polyethylene construction. Do not alter, mix with other chemicals, or dilute product or use for applications other than specified. Always protect passersby, building occupants, plantings and non-masonry surfaces from product, vapors and wind drift.

### First Aid

**Ingestion:** Do not induce vomiting. If conscious, give 3-4 glasses of water and seek immediate medical attention.

**Eye Contact:** Rinse eyes thoroughly for 15 minutes while lifting eyelids to assure thorough cleaning. Get immediate medical assistance.

**Skin Contact:** Remove contaminated clothing and rinse thoroughly for 15 minutes. Get medical attention if persistent irritation develops. Launder contaminated clothing before reuse.

**Inhalation:** Remove to fresh air. Give artificial respiration if not breathing. Get immediate medical attention.

### 24 Hour Emergency Information: INFOTRAC at 800-535-5053

**If spilled,** follow all precautionary instructions. Keep from drains. Contain, dilute with water, and neutralize with dilute alkaline source. Dispose of contaminated absorbent, container and product in accordance with local, state and federal regulations. Do not reuse empty container. Rinse before disposal.

**Shelf life:** 3 years from the date of manufacture in tightly sealed, unopened container.

## WARRANTY

The information and recommendations made are based on our own research and the research of others, and are believed to be accurate. However, no guarantee of their accuracy is made because we cannot cover every possible application of our products, nor anticipate every variation encountered in masonry surfaces, job conditions and methods used. The purchasers shall make their own tests to determine the suitability of such products for a particular purpose. PROSOCO Inc. warrants this product to be free from defects. **Where permitted by law, PROSOCO makes no other warranties with respect to this product, express or implied, including without limitation the implied warranties of merchantability or fitness for particular purpose.** The purchaser shall be responsible to make his own tests to determine the suitability of this product for his particular purpose. PROSOCO's liability shall be limited in all events to supplying sufficient product to re-treat the specific areas to which defective product has been applied. Acceptance and use of this product absolves PROSOCO from any other liability, from whatever source, including liability for incidental, consequential or resultant damages whether due to breach of warranty, negligence or strict liability. This warranty may not be modified or extended by representatives of PROSOCO, its distributors or dealers.

## CUSTOMER CARE

Factory personnel are available for product, environment and job-safety assistance with no obligation. Call 800-255-4255 and ask for Customer Care - technical support. Factory-trained representatives are established in principal cities throughout the continental United States. Call Customer Care at 800-255-4255, or visit our website at [www.prosoco.com](http://www.prosoco.com), for the name of the Enviro Klean® representative in your area.