



Technical Data Sheet

UPDATE: April 13, 2011
Make sure you have an updated data sheet on hand.
Canada and U.S. dial **1-866-212-1611** or (450) 624-1611

DESCRIPTION: **GATOR SEALER FOR CONCRETE PAVERS AND NATURAL STONES NATURAL LOOK FINISH** is made from fluorochemical polymers. This liquid penetrates deep into the concrete paver and natural stone pores, thus reducing the oil and dirt penetration, as well as protecting them from salt and calcium.

**-NATURAL FINISH
-WATER-BASED**

FEATURES:

- Easier to clean and maintain
- Non slip formula
- 3.78 L (1 U.S. gal.) covers 16 sq. m. (175 sq. ft)
- 18.9 L (5 U.S. gal.) covers 80 sq. m. (875 sq. ft)

HELPS RESIST:

- Salt and calcium
- Ultraviolet rays
- Motor oil and grease

PLEASE NOTE:

- 1) Pavers should only be sealed 60 days after their installation date.
- 2) Pavers and jointing sand **MUST** be 100% dry.
- 3) Temperature should be between 60°F / 16°C and 85°F / 29°C when sealer is applied.
- 4) First clean pavers with Gator Clean products. Remove all oil, grease and rust stains.
- 5) Use Gator Clean Efflorescence cleaner, to take away any trapped efflorescence in the paver.
- 6) Just use 1 layer of sealer because 2 layers and more might trap moisture and lead to white spots on the concrete surface.
- 7) When using Gator Seal assure yourself at least 48 hours of dry conditions prior to applying the sealer.
- 8) 3.78 L (1 gallon) of product covers an area of 16 m² (175 sq. ft.), 18.9 L (5 gallons) covers 80 m² (875 sq.ft.)



APPLICATION

1) Remove all the stains from the pavers, using Gator Clean products

INSTRUCTIONS:

- 2) Remove all contaminated jointing material and replace with Gator Polymeric Sand. Follow the instructions on the back of the bag.
- 3) Wait at least 72 hours at a minimum temperature of 60°F / 15°C and no rain for the Gator Polymeric Sand to properly harden.
- 4) Clean the entire surface with the Gator Clean Efflorescence Cleaner. This product will remove the efflorescence trapped in the concrete paver or natural stone pores as well as thoroughly clean the surface for proper sealer adhesion.
- 5) Wait at least 48 hours at a minimum temperature of 60°F / 15°C and no rain so the sand and paver surface are dry.
- 6) Apply coat of Gator Seal using a foam roller.
- 7) Let the sealer dry for 24 hours before using the sealed area.

LIMITED WARRANTY

Alliance Designer Products cannot guarantee results as it has no control over surface preparation and product application. If this product is proven to be defective, on the condition that it was applied pursuant to the required method of application and surface preparation, the sole obligation of Alliance Designer Products is to refund the purchase price. Proof of purchase is required for any claim. Alliance Designer Products shall not be liable for any other damages whatsoever, direct or consequential. To the extent permitted by law, Alliance Designer Products excludes any implied warranty of quality, merchantability or fitness for purpose.

*Please store container at above 0°C / 32°F.